



PICOFILM WO-110 MATT ZM1

matt 8003, 102 g/m²

Durable FACESTOCK film with good graphic properties for the creation of high quality product or V.I.P labels in the Home & Personal Care, Pharmaceuticals, Logistics, Oil & Chemical Industry segments as well as a variety of industrial applications.

When transporting goods by sea, long distances must be covered, often in extreme weather conditions. Labels are used to reliably mark goods of all classes, e.g. also hazardous substances or toxic chemicals, in accordance with GHS. Approval in accordance with the globally recognised BS5609 Section 3 standard for Epson CW C-4000, C-6000/6500 and C-8000 guarantees reliable, resistant labelling in the chosen printing process for such applications.

WO-110 matt ZM1 is a white 115 µm FACESTOCK BOPP film, front side matt coated for variable information printing (V.I.P.) with water-based inkjet, back side topcoat coated for increased adhesive anchorage.

End customers get a fast-drying, easy-to-use product with high colour brilliance, sharp-edged prints and very good weather resistance. It is characterised in particular by high abrasion and water resistance as well as chemical resistance.

Advantages

- High water-and abrasion resistance
- High resistance against chemicals
- BS5609 section 3 approved for Epson CW C- 4000, C-6000/6500 and C-8000
- Good weather resistance

General tips

For quality reasons PICOFILM should be stored originally packed. Storage and converting conditions of 23±5°C and 50±10% rel. humidity are recommended. Inkjet coatings are durable for a period of two years when stored appropriately in original packaging.

Physical data

Name	Value	Norm
Thickness (total) [µm]	118	ISO 534
Weight [g/m ²]	102	ISO 536

Printing instructions

We always recommend comprehensive testing of materials prior to regular conversion.

Technologies

