

PRESSURETAC TT CLASSIC 150 K

satin 7759, 155 g/m²

Linerless, self-adhesive, satin-finished paper for manual labelling as a loop tag.

PRESSURETAC TT Classic 150 K is a satin-finished, FSC® certified 155g paper with reverse coating that only sticks to itself. There is no need for waste-intensive silicone paper, making PRESSURETAC an environmentally friendly alternative to conventional self-adhesive paper.

PRESSURETAC TT Classic 150 K is supplied in roll format and can be used immediately. No punching or perforation is required when the thermal printer has a cutter or perforation blade fitted. Text or variable information is thermal transfer printed.

Advantages

- Only sticks together coating to coating (linerless)
- Reduced risk of accidents during processing as no silicone paper to discard
- Can be removed without any hint of residue – no cleaning required on wire mesh crates, cages, trays, trolleys or tensioning straps
- Ready-to-use for the final application – no punching / perforation required
- Environmentally friendly as FSC® certified and without silicone paper (linerless)



General tips

For quality reasons PRESSURETAC should be stored originally packed. Storage & converting conditions of 23±5°C and 50±10% rel. humidity are recommended.

Physical data

Name	Value	Tolerance	Norm
Weight [g/m ²]	155	±10	ISO 536
Thickness (total) [µm]	178	±10	ISO 534
Application temperature [°C]	4-40		

Durability

The product can be stored original packed for at least 9 months under these conditions.

Printing instructions

Printing and processing recommendations are available for download.

Technologies



Properties



- Sticks to itself
- Residue-free removal