

GREENGRAFX PP PRIME 170 EASYTACK

satin 3529, 170 µm

PVC-free, easy-to-bond polypropylene film

GreenGraFX PP Prime EasyTack is ideal for more environmentally friendly, PVC-free point-of-sale advertising. The easily removable EasyTack adhesive allows for simple, bubble-free application and residue-free removal from smooth surfaces. The durable, tear-resistant film is suitable for printing with solvent and UV inks, as well as for medium-term indoor use and short-term outdoor use.

Advantages

- Brilliant colour reproduction
- EasyTack - easy to apply, easily removable
- Splashproof prints for short-term outdoor applications
- Edge tear resistant
- Suitable for use on cutter plotters
- PVC free

General tips

The converting and storage should take place in a climate of 35 to 65% to relative humidity at temperatures of 10 to 30°C. Keep the product in the original packaging (cardboard box and PE bag). Cotton gloves should be worn when handling InkJet coated materials to avoid fingerprints.

Physical data

Name	Value	Norm
Thickness (film without liner / adhesive) [µm]	170	ISO 4593
Thickness (film) [µm]	330	ISO 4593
Weight (without liner/ adhesive) [g/m²]	125	ISO 536
Weight [g/m²]	280	ISO 536
Test conditions	23°C / 50% R.F.	
Adhesion strength on glass (48h) [N/25mm]	~ 0.5	FINAT No.1, 22°C
Whiteness, CIE D65/2°	82	ISO 11476

Technologies



Properties

